

農業機械用タイヤ諸元一覧表

※リムは車両メーカー採用の主要リムを記載しています。

■トラクター用

■印サイズはこの表記のパターンとなります。

タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				
T13H							
7-14	2	●		5-JA	697	162	TR413
7-16	4	●		5-JA	748	165	TR413
8-16	4	●		5-JA	804	192	TR413
8-18	4	●		W-7	849	204	TR413
8-18	4	●		W-7	849	204	TR15,TR218A
8.3-20	4	●		W-7	893	206	TR15,TR218A
9.5-20	4	●		W-8	949	240	TR15,TR218A
8.3-22	4	●		W-7	945	212	TR15,TR218A
9.5-22	4	●		W-8	995	240	TR15,TR218A
8.3-24	4	●		W-7	995	211	TR15,TR218A
9.5-24	4	●		W-8	1050	240	TR15,TR218A
11.2-24	4	●		W-10	1095	281	TR15,TR218A
■ T13HA	12.4-24	4	●	W-11	1160	310	TR15,TR218A
	12.4-24	4	●	W-11	1160	310	TR15,TR218A
	13.6-24	4	●	W-12	1210	345	TR15
■ T11H	8.3-26	4	●	W-7	1045	204	TR15
	11.2-26	4	●	W-10	1155	279	TR15
	12.4-26	4	●	W-11	1210	310	TR15,TR218A
	13.6-26	4	●	W-12	1260	340	TR15,TR218A
	13.6-28	4	●	W-12	1310	340	TR15,TR218A
	12.4-32	4	●	W-11	1360	317	TR15,TR218A

T10H							
11.2-24	4	●		W-10	1095	281	TR15,TR218A
12.4-24	4	●		W-11	1161	324	TR15,TR218A
13.6-24	4	●		W-12	1210	345	TR15
9.5-26	4	●		W-8	1100	236	TR15
11.2-26	4	●		W-10	1155	279	TR15
12.4-26	4	●		W-11	1210	310	TR15,TR218A
13.6-26	4	●		W-12	1260	340	TR15,TR218A
11.2-28	4	●		W-10	1205	279	TR15,TR218A
12.4-28	4	●		W-11	1260	317	TR15,TR218A
13.6-28	4	●		W-12	1310	340	TR15,TR218A
13.6-28	6	●		W-12	1310	340	TR15,TR218A

FSLSC							
■ FSLSD	11.2-24	4	●	W-10	1095	280	TR15,TR218A
	12.4-24	4	●	W-11	1150	314	TR15,TR218A
	13.6-24	4	●	W-12	1210	345	TR15
■ FSLS	12.4-26	4	●	W-11	1244	322	TR15,TR218A
	12.4-26	4	●	W-11	1210	315	TR15,TR218A
	13.6-26	4	●	W-12	1260	345	TR15,TR218A
	12.4-28	4	●	W-11	1262	314	TR15,TR218A
	13.6-28	6	●	W-12	1310	345	TR15,TR218A
■ FSLS	14.9-28	6	●	W-13	1406	380	TR218A
	16.9-30	6	●	W-15L	1512	429	TR218A
	12.4-32	4	●	W-11	1358	315	TR218A
	12.4-32	6	●	W-11	1358	315	TR218A
	12.4-36	6	●	W-11	1465	319	TR218A
	13.6-38	6	●	W-12	1578	348	TR218A

FH80							
18.4-34	6	●		W-16L	1635	467	TR218A

FSLH							
8-18	4	●		W-7	840	207	TR15,TR218A
12.4-24	6	●		W-11	1150	317	TR15,TR218A
16.9-34	6	●		W-15L	1587	440	TR218A
14.9-38	6	●		W-13	1618	390	TR218A

FSLM							
4.50-10	4	●		3.00D	510	120	TR13
6-10	4	●		5-JA	550	155	TR13
5-12	2	●		4-JA	550	123	TR13
5-12	4	●		4-JA	550	123	TR13
5.00-12	2	●		3.00D	581	131	TR13
5.00-12	4	●		3.00D	581	131	TR13
6-12	4	●		5-JA	600	155	TR13
6.00-12	4	●		4.00E	636	162	TR13
6.00-12	6	●		4.00E	638	163	TR13
5-14	4	●		4-JA	605	128	TR13
6-14	2	●		5-JA	653	155	TR13
6-14	4	●		5-JA	653	158	TR13
7-14	4	●		5-JA	690	174	TR13
7-16	4	●		5-JA	740	170	TR15,TR218A
8-16	4	●		5-JA	789	197	TR15,TR218A
4.00-18	4	●		2.75D	690	108	TR15
8-18	4	●		W-7	840	207	TR15,TR218A
8-18	6	●		W-7	840	207	TR15,TR218A
7.2-20	4	●		W-6	845	179	TR15
8.3-20	4	●		W-7	890	209	TR15,TR218A
8.3-20	6	●		W-7	890	209	TR15,TR218A
9.5-22	6	●		W-8	996	242	TR15,TR218A
9.5-24	6	●		W-8	1047	242	TR15,TR218A

タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				
FSLF							
7-16	4	●		5-JA	740	170	TR15,TR218A
7-16	4	●		6.00F	740	180	TR15,TR218A
8-16	4	●		5-JA	790	193	TR15,TR218A
9.5-16	4	●		W-8	845	248	TR15,TR218A
12.4-16	4	●		W-11	964	325	TR218A
11.2-24	4	●		W-10	1088	274	TR15,TR218A
11.2-24	6	●		W-10	1088	274	TR15,TR218A
5-26	4	●		4-JA	900	122	TR15A

FSLW							
7.2-20	4	●		W-6	845	179	TR15
11.2-24	4	●		W-10	1088	280	TR15,TR218A
11.2-24	6	●		W-10	1088	285	TR15,TR218A

FSL							
11.2-28	4	●		W-10	1206	287	TR15,TR218A
11.2-28	6	●		W-10	1206	287	TR15,TR218A
12.4-28	4	●		W-11	1262	320	TR15,TR218A
12.4-28	6	●		W-11	1262	320	TR15,TR218A
14.9-28	6	●		W-13	1370	387	TR218A
16.9-30	6	●		W-15L	1485	436	TR218A
12.4-32	6	●		W-11	1364	320	TR218A
12.4-36	6	●		W-11	1465	320	TR218A
13.6-38	6	●		W-12	1574	345	TR218A

FLOO							
7-16	6	●		5-JA	740	173	TR15,TR218A
8-16	4	●		5-JA	790	193	TR15,TR218A
9.5-16	6	●		W-8	845	243	TR15,TR218A
9.5-18	4	●		W-8	895	243	TR15,TR218A
9.5-18	6	●		W-8	895	243	TR15,TR218A
8.3-20	6	●		W-7	890	211	TR15,TR218A
9.5-20	6	●		W-8	945	243	TR15,TR218A
11.2-20	6	●		W-10	1003	284	TR218A
8.3-22	6	●		W-7	945	210	TR15,TR218A
9.5-22	4	●		W-8	995	243	TR15,TR218A
9.5-22	6	●		W-8	995	243	TR15,TR218A
8.3-24	6	●		W-7	993	205	TR15,TR218A
9.5-24	6	●		W-8	1050	243	TR15,TR218A
11.2-24	6	●		W-10	1088	275	TR15,TR218A
12.4-24	4	●		W-11	1155	320	TR15,TR218A
12.4-24	6	●		W-11	1155	320	TR15,TR218A
13.6-24	4	●		W-12	1210	350	TR15
13.6-24	6	●		W-12	1210	345	TR15
14.9-24	6	●		W-13	1247	383	TR218A
13.6-26	4	●		W-12	1260	355	TR15,TR218A
12.4-28	6	●		W-11	1260	320	TR15,TR218A
13.6-28	4	●		W-12	1310	345	TR15,TR218A
13.6-28	6	●		W-12	1310	345	TR15,TR218A
14.9-28	6	●		W-13	1365	380	TR218A
16.9-28	6	●		W-15L	1400	442	TR218A
16.9-30	6	●		W-15L	1485	442	TR218A
18.4-30	6	●		W-16L	1547	487	TR218A
12.4-32	6	●		W-11	1360	320	TR218A
16.9-34	6	●		W-15L	1587	440	TR218A
18.4-34	6	●		W-16L	1635	478	TR218A
13.9-36	6	●		W-12	1478	343	TR218A
15.5-38	6	●		W-14L	1582	394	TR218A
16.9-38	8	●		W-15L	1671	442	TR218A

FSR							
4.00- 9	2	●		3.00D	458	114	TR13
4.50-10	4	●		3.00D	488	120	TR13
4.00-12	4	●		3.00D	538	113	TR13
4.00-15	4	●		3.00D	613	113	TR15
5.00-15	4	●		3.00D	660	133	TR15
6.00-16	4	●		4.00E	737	167	TR15
6.50-16	6	●		4.50E	763	180	TR15
7.50-16	6	●		5.50F	815	210	TR15
6.00-19	6	●		4.00E	818	164	TR15

FSM							
7.50-16	6	●		5.50F	808	211	TR15

トラクター

耕うん機

インプラメント

田植機

収穫機(バインダー)

草刈り機・ゴルフカート

農用運搬車・不整地走行車

荷車

農業機械用タイヤ諸元一覧表

※リムは車両メーカー採用の主要リムを記載しています。

■ 耕うん機用

タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				
U10L							
5-12	2	●	●	4-JA	545	126	TR13 (W/T), TR413 (T/L)
5.00-12	2	●	●	3.00D	573	131	TR13 (W/T), TR413 (T/L)
6-12	2	●	●	5-JA	600	158	TR413
6.00-12	2	●	●	4-JA	629	154	TR13 (W/T), TR413 (T/L)
TA10							
4.00-12	2		●	3.00D	525	111	TR413
A10L							
3.00-12	4	●		1.85	457	70	TR4
TA							
3.50- 5	2	●		3.00SP	300	100	TR875
3.50- 6	2	●	●	3.00SP	320	93	TR13 (W/T), TR413 (T/L)
100/85D6	2		●	3.00	330	100	TR413
3.50- 7	2	●	●	3.00D	347	98	TR13 (W/T), TR413 (T/L)
4.00- 7	2	●	●	3.00D	397	110	TR13 (W/T), TR413 (T/L)
4.00- 8	2	●	●	3.00D	435	111	TR13 (W/T), TR413 (T/L)
4.00- 9	2	●	●	3.00D	458	111	TR13 (W/T), TR413 (T/L)
4.00-10	2	●	●	3.00D	483	111	TR13 (W/T), TR413 (T/L)
4.50-10	2	●	●	3.00D	510	123	TR13
4.00-12	2	●	●	3.00D	540	111	TR13 (W/T), TR413 (T/L)
5-12	2	●		4-JA	550	125	TR13
5.00-12	2	●	●	3.00D	581	133	TR13 (W/T), TR413 (T/L)
6-12	2	●	●	5-JA	600	158	TR13 (W/T), TR413 (T/L)
6.00-12	2	●	●	4.00E	636	157	TR13 (W/T), TR413 (T/L)
6-14	2	●		5-JA	657	162	TR13
AL○○							
4.00-16	2	●		3.00D	650	108	TR15
4.40-21	2	●		2.75D	800	118	TR13
4.40-21	4	●		2.75D	800	120	TR13
130/90-21AG	-	●		2.75D	800	120	TR13
AR○○							
3.50- 5	2	●	●	3.00SP	308	93	TR875 (W/T), TR413 (T/L)
4.00- 7	2	●		3.00D	400	111	TR13
4.00- 8	2	●		3.00D	445	111	TR13
4.00-10	2	●		3.00D	492	111	TR13
4.50-10	2	●		3.00D	515	118	TR13
4.00-12	2	●		3.00D	540	110	TR13
5-12	2	●		4-JA	550	125	TR13
5.00-12	2	●		3.00D	581	133	TR13
6-12	2	●		5-JA	600	158	TR13
6.00-12	2	●		4.00E	636	157	TR13
6.00-12	4	●		4.00E	636	160	TR13
5-14	4	●		4-JA	605	128	TR15
6-14	4	●		5-JA	653	155	TR13

■ インプリメント(牽引車)用

タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				
FI 2							
11.5/80-15	10		●	10-JJ	842	332	TR413
FI 3							
9.00-15	8	●		6-LB	850	252	TR15
AL							
9.00-13	6	●		5-1/2K	792	254	TR15

■ 田植機用

■印サイズはこの表記のパターンとなります。

タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				
AT○○							
3.00-16	4	●		1.85	620	76	TR4
2.50-17	4	●		1.60A	604	60	TR4
2.75-17	4	●		1.85	600	70	TR4S
3.00-17	4	●		1.85	650	76	TR4
2.50-18	4	●		1.60A	625	60	TR4
3.00-23	4	●		MT1.85	765	80	TR4S
3.00-25	4	●		SP1.85	815	76	TR4S
3.00-26	4	●		MT1.85	865	80	TR4S
3.00-28	4	●		MT1.85	900	80	TR4

R13LA

76× 12/6-23	4	●		1.70	764	60	TR4S
81× 18/6-25	4	●		1.70	810	60	TR4S
87× 18/6-27	4	●		1.70	865	64	TR4S
92× 18/6-29	4	●		1.70	915	60	TR4S
■ R13LB 60/100-25AG	-	●		1.70	810	60	TR4S
60/100-31AG	-	●		1.70	970	60	TR4S

R12L

62× 12/A-15	4	●		MT2.75	624	108	TR4
56× 6/6-16	4	●		1.40	556	55	TR4S

R14L

60/90-25AG	-	●		1.70	795	63	TR4S
60/90-27AG	-	●		1.70	850	63	TR4S

R16L

120/90-26AG	-	●		4-JA	940	125	TR15
-------------	---	---	--	------	-----	-----	------

■ 収穫機(バインダー)用

■印サイズはこの表記のパターンとなります。

タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				
PL							
16× 7.00- 8	2	●	●	5.50	403	180	TR13 (W/T), TR413 (T/L)
16× 7.00- 8	4	●		5.50	403	170	TR13
17× 7.00- 8	2		●	5.50	435	185	TR413
18× 7.00- 8	2		●	5.50	435	185	TR413
19× 8.00- 8	2		●	7.00	480	210	TR413
19× 10.00- 8	2		●	8.50	480	260	TR413

PL3

16× 10.00- 8	2		●	8.50	410	255	TR413
--------------	---	--	---	------	-----	-----	-------

PF

17× 7.0- 8	-		●	5.50	430	170	TR413
18× 7.0- 8	-		●	6.50	455	175	TR413
19× 7.00- 8	-		●	6.50	480	180	TR413

B10L

18× 8.0- 8	-		●	6.50	420	200	TR413
18× 10.0- 8	-		●	5.50	420	235	TR413
19× 11.0- 8	-		●	9.00	460	270	TR413

PFH

18× 7.0- 8	-		●	5.50	427	180	TR413
■ PFHB 18× 9.0- 8	-		●	7.50	440	233	TR413
■ PFHB 18× 12.0- 8	-		●	10.50	440	305	TR413

FTI

18× 7.0- 8	-		●	3.00	460	175	TR413
18× 10.0- 8	-		●	5.50	445	250	TR413
19× 9.0- 8	-		●	4.50	464	235	TR413
20× 8.0-10	-		●	4.00	485	205	TR413

■ 草刈機・ゴルフカート用

タイヤサイズ	プライ	構造		適用リム※	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				

SO

18× 9.50- 8	2		●	7.00I	433	223	TR413
-------------	---	--	---	-------	-----	-----	-------

PD

13× 6.00- 8	2		●	5.00	342	148	TR413
18× 7.00- 8	2		●	5.50	457	170	TR413
18× 7.00- 8	4		●	5.50	457	170	TR413
18× 7.00- 8	6		●	5.50	460	177	TR413
18× 8.50- 8	4		●	7.00I	452	213	TR413
18× 9.50- 8	4		●	7.00	464	230	TR413
19× 8.00-10	2	●		7.00D	490	210	JS2
19× 8.00-10	4		●	7.00D	490	217	TR413
20× 8.00-10	4	●		5.00D	503	180	TR13
20× 8.00-10	4		●	7.00I	503	200	TR413
23× 8.50-12	4		●	7.00I	578	213	TR413
27× 8.50-15	4	●		7.00I	684	214	TR15

PD5

13× 5.00- 6	2		●	3.50A	320	122	TR413
16× 6.50- 8	2		●	5.375I	406	165	TR413
16× 6.50- 8	6		●	5.375I	415	168	TR413

PD1

16× 6.50- 8	2		●	5.375I	406	165	TR413
16× 6.50- 8	4		●	5.375I	411	165	TR413
16× 4.50- 9	2	●		3.00D	401	104	TR13
20.5× 8.00-10	4		●	6.00I	533	205	TR413
22× 8.50-12	4		●	7-JA	552	212	TR413
23× 10.50-12	4		●	8-1/2JA	589	264	TR413
24× 8.50-12	4		●	7-JA	606	219	TR413
24× 8.50-14	4		●	7-JA	604	216	TR413
25× 8.50-14	4		●	7-JA	646	219	TR413
27× 8.50-15	4		●	7-JA	684	220	TR413
29× 12.00-15	4		●	10-LB	750	307	TR413
31× 13.5-15	4		●	10-LB	793	342	TR413
31× 15.5-15	4		●	13-LB	790	397	TR413
215/80D15	4	●		7-JA	721	215	TR15
13.6-16	4	●		W-12	997	357	TR218A
355/80D20	4	●		W-11	1076	345	TR218A
475/65D20	4	●		W-15L	1126	465	TR218A

PD3

14× 5.00- 6	2		●	3.50A	350	125	TR413
18× 8.50- 8	2		●	7.00	448	213	TR413

M40B

16× 6.50- 8	2		●	5.375I	406	165	TR413
16× 6.50- 8	4		●	5.375I	411	165	TR413
20× 10.00- 8	2		●	8.5-JA	506	261	TR413
20× 10.00- 8	4		●	8.5-JA	500	265	TR413
20× 8.00-10	4		●	6.00I	502	193	TR413
23× 8.50-12	4		●	7-JA	578	216	TR413
23× 10.50-12	4		●	8.5-JA	589	264	TR413
24× 8.50-12	4		●	7-JA	620	222	TR413
315/75D15	4		●	10-LB	853	316	TR413
315/80D16	6		●	10-LB	910	316	TR413

M50G

31× 13.5-15	6		●	10-LB	777	340	TR413
-------------	---	--	---	-------	-----	-----	-------

FD

6-12	4	●		5-JA	605	164	TR13
6-14	4	●		5-JA	654	163	TR13
8-16	4	●		6.00F	790	208	TR15
11.2-24	4	●		W-10	1071	285	TR15,TR218A
13.6-28	6	●		W-12	1287	355	TR218A

PR

11× 4.00- 5	2		●	3.00	272	97	TR413
14× 5.00- 6	2		●	3.50A	350	125	TR413
18× 8.50- 8	4		●	7.00I	445	213	TR413

PD2

21× 11.00-10	2	●	●	8.50I	528	274	TR13(W/T),TR413(T/L)
--------------	---	---	---	-------	-----	-----	----------------------

■ 農用運搬車・不整地走行車用

タイヤサイズ	プライ	構造		適用リム※	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				

FG

19× 7.50- 8	2		●	5.50E	480	177	TR13
19× 10.00- 8	2		●	8.50	485	255	TR13

FM1

17× 8.00- 8	4		●	7.00	440	208	TR413
-------------	---	--	---	------	-----	-----	-------

FM2

17× 8.00- 8	4		●	7.00	442	203	TR413
-------------	---	--	---	------	-----	-----	-------

FM3

23× 9.00-12	4		●	7-JA	581	215	TR13
-------------	---	--	---	------	-----	-----	------

K10H

26× 10.00-12	8		●	8.5-JA	660	260	TR13
--------------	---	--	---	--------	-----	-----	------

荷車用タイヤ諸元一覧表

※リムは車両メーカー採用の主要リムを記載しています。

■ 荷車用

■印サイズはこの表記のパターンとなります。

タイヤサイズ	プライ	構造		適用リム※	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
		W/T	T/L				

UL

2.50- 4	4		●	1.75	225	63	TR87S
2.75- 4	2		●	1.75	234	70	TR87S
3.00- 4	4		●	2.10(1.75)	256(247)	82(78)	TR87S
3.50- 5	2		●	3.00SP	289	92	TR87S
3.50- 5	4		●	3.00SP	290	94	TR87S
■ PD3	4.00- 5	2	●	3.00SP	320	105	TR87S,TR244
	4.00- 5	4	●	3.00SP	310	102	TR87S,TR244
	3.25- 8	2	●	2.10	366	84	JS87
	4.00- 8	4	●	3.00D	410	111	JS244A,TR13
	4.00- 8	6	●	3.00D	410	111	JS244A,TR13
■ ULS	5.00- 8	4	●	3.50D	469	138	JS2
■ ULS	5.00- 9	6	●	3.50D	497	141	JS2
	6.00- 9	6	●	4.00E	546	163	JS2
	4.50-14	4	●	3.00D	585	123	TR15
	4.50-14	6	●	3.00D	582	120	TR15
	5.00-14	6	●	3.50D	617	140	TR15
	3.25-16	4	●	1.85B	590	88	TR4
	3.50-16	4	●	1.85B	601	92	TR4
	4.00-16	4	●	2.15B	622	108	TR4
	4.50-16	6	●	3.00D	647	123	TR4
	5.00-16	6	●	3.00D	676	135	TR15

DC

3.50-5	2		●	3.00SP	294	98	TR87S
--------	---	--	---	--------	-----	----	-------